

Verwendung:

Für Anwendungen bei erhöhten Temperaturen in Berührung mit Wasser wie auch im Lebensmittel- und pharmazeutischen Bereich.

Hochtemperaturbeständig! 250°C permanent, kurzzeitig bis über 300°C

O-RINGE



Artikel Nr.	Innenmaße [mm]	Aussenmaße [mm]
	Ø id	Ø ad
B-2241-0000	5,5	1,0
B-1956-0000	8,0	2,0
B-1535-0000	8,0	4,0
B-2275-0000	8,0	5,0
B-2567-0000	9,0	2,5
B-0820-0000	10,0	3,0
B-1847-0000	12,0	2,2
B-0794-0000	12,0	3,0
B-1559-0000	14,5	4,0
B-2047-0000	20,0	4,0
B-0904-0000	23,0	4,0
B-0905-0000	31,0	4,0
B-1511-0000	34,5	4,5
B-0906-0000	38,0	4,0
B-0907-0000	49,0	4,0
B-2570-0000	50,0	4,0
B-2586-0000	54,0	4,0
B-0908-0000	59,0	4,0
B-0909-0000	78,0	4,0
B-1676-0000	100,0	6,0
B-2215-0000	114,0	4,0
B-1709-0000	129,0	3,0

TECHNICAL SILICONE PARTS

SILROC CZ[®]
the world of silicone

GRUPPE O - O-RINGE

www.silroc.cz



O-RINGE

Artikel Nr.	Innenmaße [mm]	Aussenmaße [mm]
	Ø id	Ø ad
B-2280-0000	130,0	4,0
B-1587-0000	130,0	5,0
B-1636-0000	138,0	6,0
B-2013-0000	160,0	3,0
B-2281-0000	165,0	4,0